



Details	
Model	: ASPIRE-3000SP
Power	: 3kVA
Technology	: On-line 'double conversion'
Design	: Tower & Rack Convertible
Input	
Nominal Voltage	: 220Vac / 230Vac / 240Vac
Frequency	: 45 - 65 Hz
Power Factor	: 0.99
Output	
Nominal Voltage	: 220Vac / 230Vac / 240Vac
Wave Form	: Pure Sine Wave
Total Harmonic Distortion	: < 3%
Frequency	: 50/60 Hz
Frequency Regulation	: ± 0.1%
Static Voltage Regulation (0% - 100% load)	: < 1%
Crest Factor	: 3.1
Transfer Time	: 0 sec
Overload	: Up to 30 secs @ 100% - 120%
	: Up to 10 secs @ 120% - 150%
	: Transfer to bypass @ >150%
Total Efficiency	: Up to 85%
Battery	
Type	: Maintenance-free lead acid batteries
Recharge Time	: 3 hrs up to 90%
Voltage	: 72 VDC
Cold Start	: Present
Display	
LED + LCD Display	: Utility or Bypass, Battery Low, Battery Abnormal, Overload, Site Wiring Fault, Service Mode, UPS Off, UPS Abnormal
LCD Display	: Input / Output Voltage and Frequency Values, Load %, Battery Voltage, Internal Temperature
Environment	
Operating Temperature	: 0°C... + 40°C
Proposed Temperature to extend battery life	: 20°C - 25°C
Humidity	: up to 90% (non-condensing)
Audible Noise at 1m	: < 50 dB
Physical Specifications	
Net Weight	: 30kg
Dimension (mm)	: 440 x 88 x 650

ACTCO Pte Ltd

Blk 9003 Tampines Street 93, Tampines Industrial Park A, #02-174/176, Singapore 528837

Tel: (65) 6746 5080 | Fax: (65) 6746 2966

General: helpdesk@actco.com.sg | Sales: sales@actco.com.sg