

## The Solution for Large Centralised Systems

Adjacent to PoDs, iSTS Model K feeds a single level of distribution or are used in pairs to improve availability in dual corded distribution systems.

Ideally suited for corridors and computer rooms with just 400mm in depth.



## Key features

- Fuseless design
- Built-in transient voltage protection
- UPS Eco-Mode compatible
- Safe asynchronous source transfers
- Very high MTBF (>800,000 hours)
- LED mimic decal with graphic LCD interface
- One touch transfers
- Visual and sound alarm
- Integrated web server
- Remote operation
- High-level interface - MODBUS, SNMP
- Email alerts
- Clock synchronisation with NTP
- Mechanically interlocked circuit breakers Maintenance bypass
- Redundant fan cooling
- High fault current capacity
- 5 x voltage free contacts & remote inputs
- Easy front access for maintenance
- Australian designed & manufactured

## Available options

- Top entry



<b>Current rating</b>	1Ph: 630A max 3Ph: 630A max
<b>Voltage rating</b>	All region-specific voltages selectable $\pm 10\%$
<b>Type</b>	1-Phase/2-Pole, 3-Phase/3-Pole or 3-Phase/4-Pole
<b>Frequency</b>	50Hz and 60Hz, $\pm 10\%$ - Auto detection
<b>Transfer type</b>	Break-Before-Make zero current transfer by Thyristors / SCR
<b>Synchronous break time</b>	<1ms - asynchronous break time up to $\frac{1}{4}$ cycle
<b>MTBF</b>	>800,000 hours
<b>Maintenance bypass</b>	5 Mechanically interlocked circuit breakers
<b>Isolation</b>	Incoming sources and output isolator switches
<b>Display</b>	Bi-colour LED mimic decal with graphic backlit LCD display and information interface
<b>Interface</b>	Preferred supply selection, Source transfer selection and Alarm cancel button
<b>Contact</b>	2 Self wetting transfer control inputs 5 Voltage free change-over status indicators, Form C
<b>Ethernet</b>	HTTP, SNMP, MODBUS TCP, Email & NTP
<b>Input options</b>	Terminals M10 via gland plate
<b>Output options</b>	Terminals M10 via gland plate
<b>Dimensions H x W x D</b>	1900 x 800 x 400mm
<b>Weight</b>	195kg - 295kg
<b>Temperature</b>	0 – 45°C
<b>IP rating</b>	IP21
<b>Detection</b>	Digital: <1ms
<b>Asynchronous break time</b>	0ms, 10ms, 50ms or Vt proportional, 0° to 180°
<b>Loading</b>	0 - 100% @45°C ambient
<b>Device ratings</b>	1800A <sub>RMS</sub> @28kA 1 cycle
<b>Overload @40°C ambient</b>	125% for 10min 4kA for 1s 150% for 30s 8kA for 0.1s 28kA for 1 cycle
<b>Fault current setting</b>	350% peak with load fault transfer inhibit
<b>Safe install environment</b>	28kA for 1 cycle - Fuseless design
<b>Protection</b>	Circuit breakers
<b>Power factor</b>	No practical limit
<b>Max THDV</b>	10% - Max allowable source voltage distortion
<b>Crest factor</b>	3.5 : 1
<b>dV/dt max</b>	800V/ $\mu$ s
<b>Cooling</b>	Redundant fans
<b>Humidity @40°C ambient</b>	5 – 95% non-condensing
<b>Regulatory approvals</b>	IEC 62310-1,2,3 - IEC 60950 - IEC 61000-6-1,2,3,4 – CE – RCM - UL Capable - RoHS
<b>Standard warranty</b>	24 months offsite repair or replacement policy

Specifications are subject to change without notice