

## The Industrial Wall Mount Solution

Generally dedicated to a single sensitive application where power continuity is critical. iSTS model C rugged design is adapted to all industrial environments.

Compact, wall mounted, iSTS Model C frees floor space



## Key features

- Fuse-less
- Space saving wall-mount design
- Built-in transient voltage protection
- UPS Eco-Mode compatible
- Safe asynchronous source transfers
- Very high MTBF (>800,000 hours)
- LED mimic decal with graphic LCD interface
- One touch transfers
- Visual and sound alarm
- Integrated web server
- Remote operation
- High-level interface - MODBUS, SNMP
- Email alerts
- Clock synchronisation with NTP
- Maintenance bypass with mechanically interlocked 5 x circuit breakers
- Redundant fan cooling
- 5 x voltage free contacts & remote inputs
- Easy access for maintenance
- Australian designed & manufactured

## Available options

- Top entry



<b>Current rating</b>	1Ph: 250A max 3Ph: 160A max	
<b>Voltage rating</b>	All region-specific voltages selectable $\pm 10\%$	
<b>Type</b>	1-Phase/2-Pole, 3-Phase/3-Pole or 3-Phase/4-Pole	
<b>Frequency</b>	50Hz and 60Hz, $\pm 10\%$ - Auto detection	
<b>Transfer type</b>	Break-Before-Make zero current transfer by Thyristors / SCR	
<b>Synchronous break time</b>	<1ms - asynchronous break time up to $\frac{1}{4}$ cycle	
<b>MTBF</b>	>800,000 hours	
<b>Maintenance bypass</b>	5 Mechanically interlocked circuit breakers	
<b>Isolation</b>	Incoming sources and output isolator switches	
<b>Display</b>	Bi-colour LED mimic decal with graphic OLED display and information interface	
<b>Interface</b>	Preferred supply selection, Source transfer selection and Alarm cancel button	
<b>Contact</b>	2 Self wetting transfer control inputs 5 Voltage free change-over status indicators, Form C	
<b>Ethernet</b>	HTTP, SNMP, MODBUS TCP, Email & NTP	
<b>Input options</b>	Fixed wiring to terminals up to 95mm <sup>2</sup> cables via glands	
<b>Output options</b>	Fixed wiring to terminals up to 95mm <sup>2</sup> cables via glands	
<b>Dimensions H x W x D</b>	800 x 600 x 400mm	
<b>Weight</b>	60kg - 97kg	
<b>Temperature</b>	0 – 45°C	
<b>IP rating</b>	IP21	
<b>Detection</b>	Digital: <1ms	
<b>Asynchronous break time</b>	0ms, 10ms, 50ms or Vt proportional, 0° to 180°	
<b>Loading</b>	0 - 100% @45°C ambient	
<b>Device ratings</b>	1250A <sub>RMS</sub> , 1800V, 20kA 1 cycle	
<b>Overload @40°C ambient</b>	125% for 10min 1kA for 1s	150% for 30s 20kA for 1 cycle
<b>Fault current setting</b>	350% peak with load fault transfer inhibit	
<b>Safe install environment</b>	20kA for 1 cycle - Fuseless design	
<b>Protection</b>	Circuit breakers	
<b>Power factor</b>	No practical limit	
<b>Max THDV</b>	10% - Max allowable source voltage distortion	
<b>Crest factor</b>	3.5 : 1	
<b>dV/dt max</b>	800V/ $\mu$ s	
<b>Cooling</b>	Redundant fans	
<b>Humidity @40°C ambient</b>	5 – 95% non-condensing	
<b>Regulatory approvals</b>	IEC 62310-1,2,3 - IEC 60950 - IEC 61000-6-1,2,3,4 – CE – RCM - UL Capable - RoHS	
<b>Standard warranty</b>	24 months offsite repair or replacement policy	

Specifications are subject to change without notice